

## DEFORT CIR-35

### Scales inhibitor for water circuits

#### CHARACTERISTICS

DEFORT CIR-35 is produced with a special formula that prevents lime scales from forming in closed circuit due to water hardness in boilers, condensers, cooling towers, etc. It protects against corrosion and reduces the formation of sludge.

#### HOW TO USE

Add DEFORT CIR-35 to the circuit, once is clean, according to the following dosages:

Boilers: Add 250 ml of product per 1000 litres of water per 10 °HF hardness.

Cooling towers: Add 125 ml of product per 1000 litres of water per 10 °HF hardness.

#### PROPIEDADES FISICO-QUIMICAS

Appearance	Liquid
Colour	Yellow
Odour	Odourless
pH (10%)	11,4
Density (20°C)	1160 kg/m <sup>3</sup>
Solubility	Soluble in water

#### PRESENTATION CONATINER

10 and 20 litres container

#### PRECAUTION



**Hazard statements:** Eye Dam. 1: H318 - Causes serious eye damage.  
Skin Irrit. 2: H315 - Causes skin irritation.

**Precautionary statements** P264: Wash thoroughly after handling.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P302+P352: IF ON SKIN: Wash with plenty of water.  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing.  
P310: Immediately call a POISON CENTER/doctor  
P332+P313: If skin irritation occurs: Get medical advice/attention. Do not ingest. Keep out of the reach of children. In case of accident, consult to the Medical Service of Toxicological Information Tel. 0034 915620420.

**Contains:** Tetrasodium ethylenediaminetetraacetate.

#### ADDITIONAL INFORMATION

While the above information is correct to our criteria, as the conditions of use of the product are beyond our control, we disclaim any responsibility for incorrect use of the product.