

DEFORT DC-SH

Floor acid pickling

CHARACTERISTICS

Pickling and acidic cleaner for all types of soils that do not evolve irritant or corrosive vapours. It prepares surfaces for further crystallize and/or wax processing. It removes easily and completely eliminates limescale, plaster, cement, rust and other debris which can alter the crystallize process

With 1 liter can be treated between 30-40 m², depending on soil and porosity of the pavement.

HOW TO USE

Apply it dissolved in water, between 10-20 %, depending on scale and soil quality. Treat small areas with scrubber or rotary machine, using black or brown disk, rinsing quickly with water to avoid prolonged contact of the product on the surface. It is very important the complete removal of the etchant, since any residue thereof may effect subsequent polishing treatment.

PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid
Colour	Yellow
Odour	Characteristic
pH (10 %)	1.09
Density (20 °C)	1095 kg/m ³
Water solubility	Soluble in water

PRESENTATION

5 litres container

PRECAUTION

Warning



Hazard statements: Eye Irrit. 2: H319 - Causes serious eye irritation. Met. Corr. 1: H290 - May be corrosive to metals. Skin Irrit. 2: H315 - Causes skin irritation.

Precautionary statements: P234: Keep only in original packaging. P264: Wash thoroughly after use. P280: Wear protective gloves/protective clothing/eye protection/face protection. P302+P352: IF ON SKIN: Wash with plenty of soap and water. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P390: Absorb spillage to prevent material damage. Do not ingest. Keep out of the reach of children. In case of accident, consult to the Medical Service of Toxicological Information Tel. 0034 915620420.

ADDITIONAL INFORMATION

While the above information is correct to our criteria, as the conditions of use of the product are beyond our control, we disclaim any responsibility for incorrect use of the product.