

## EUROSANEX, S.L.

Pol. Ind. Castilla · Vial 2 · Vial 5 46380 Cheste (Valencia) · Spain Tel. +34 962 510 407 Fax +34 962 512 521 correo@eurosanex.com www.eurosanex.com

## **Technical data sheet**

FFP2 MASK - Case 10 ut



## **General characteristics**

- Personal Protective Equipment (PPE) with CE 0598 certificate, manufactured with 5 layers and protection level FFP2 NR for particles, solid and liquid aerosols, with filtration efficiency ≥ 94% (particles up to 0.6 microns).
- Complies with the harmonized European standard for respiratory protection EN 149:2001+A1-2009 and Regulation (UE) 2016/425.
- The purpose of the PPE masks is to filter the inhaled air avoiding the entry of polluting particles into our body and they are used to prevent contagion of various pathological agents: influenzavirus A, influenzavirus B, avian influenza, coronavirus, (MERS-CoV, SARS-CoV (SARS), SARS-CoV-2 (COVID-19), *Yersinia pestis* and tuberculosis.
- Manufactured under a strict quality protocol in its production supervised annually by an accredited entity to guarantee certified protection.
- Ergonomic and very adaptable to the face, it incorporates an aluminium nose clip and elastic straps to guarantee a perfect seal.
- Indicated for daily use during an entire work shift. Not reusable.
- Do not use the mask if it is deformed or if it becomes damp or deteriorates due to use.

FFP2 MASK - Case 10 ut	
Code	MDS 9700
Filtration efficiency	FFP2 - ≥ 94%
Material 1st outer layer	Spunlace of 50 g
2nd layer material	Meltblown of 25 g
3rd layer material	Meltblown of 25 g
4th layer material	Hot air cotton of 45 g
5th inner layer material	Spunlace special for contact with the skin of 25 g
Colour	White
Subjection	2 elastic side fastening and nose closure clip
Measurements	164 x 106 mm
Packaging	Individually wrapped and kits of 10 ut
Boxes	100 kits per box (Total 1,000 masks)