

KENEX CPL

Copolymer protection cleaner

CHARACTERISTICS

Product specially formulated to remove the polymer layer that protects certain brands vehicles.

HOW TO USE

Wash the car body before applying the product in order to remove all traces of sand or dirt that might scratch the painting during the process of polymers removal. Spray the product over the body of the vehicle with KENEX CPL diluted in water, with a proportion between 25-50%. Leave it act for a few seconds, rubbing afterwards with a sponge or cloth until complete removal of the polymer layer. Then, wash with pressured water, rinsing with water to obtain great results.

PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid
Colour	Blue
Odour	Odourless
pH (10%)	12
Density (20°C)	1065 kg/m ³
Solubility	Easily soluble in water

PRESENTATION

10 and 20 litres containers

PRECAUTIONS



Hazard statements: Eye Dam. 1: H318 - Causes serious eye damage. Skin Irrit. 2: H315 - Causes skin irritation.

Precautionary statements: P264: Wash thoroughly after use. P280: Wear protective gloves/protective clothing/eye protection/face protection. P302+P352: IF ON SKIN: Wash with plenty of water. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310: Immediately call a POISON CENTER or doctor/physician. P332+P313: If skin irritation occurs: Get medical advice/attention. Do not ingest. Keep out of the reach of children. In case of accident, consult to the Medical Service of Toxicological Information Tel. 0034 915620420.

Substances that contribute to the classification: Sodium metasilicate pentahydrate; Ethoxylated Undecyl Alcohol; 1-Propanaminium, 3-amino-N-(carboxymethyl)-N,N-dimethyl-, N-(C12-18(even numbered) acyl) derivs., hydroxides, inner salts.

ADDITIONAL INFORMATION

While the above information is correct to our criteria, as the conditions of use of the product are beyond our control, we disclaim any responsibility for incorrect use of the product.