KENEX DL

Dielectric clearing product

CHARACTERISTICS

It is a powerful cleaner with high dielectric strength, formulated for the maintenance, cleaning and degreasing of circuits, frames and electric engines on which it acts by displacing the existing humidity, protecting the treated elements from oxidation. It does not attack the metals, it does not damage the insulating materials nor the varnishes of the armatures and windings.

HOW TO USE

It is advisable to pre-clean with pressurized air to remove dust and dirt. KENEX DL is then applied by spraying, brushing or dipping, allowing the excess product to drain, and drying with air under pressure can be favoured.

PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Oily liquid
Colour	Colourless
Odour	Odourless
pH	Not relevant
Density (20ºC)	732 kg/m^3
Water solubility	Insoluble in water and soluble in organic solvents.

PRESENTATION

5 and 10 litres containers

PRECAUTION

Danger

Hazard indications: Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways Flam. Liq. 3: H226 - Flammable liquid and vapour. EUH066: Repeated exposure may cause skin dryness or cracking.
Cautionary advice: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P280: Wear protective gloves/protective clothing/eye protection/face protection. P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor. P370+P378: In case of fire: Use ABC powder extinguisher to extinguish. P403+P235: Store in a well-ventilated place. Keep cool. P501: Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively.
Substances that contribute to the classification: Decane; Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

ADDITIONAL INFORMATION

While the above information is correct to our criteria, as the conditions of use of the product are beyond our control, we disclaim any responsibility for incorrect use of the product.

THINK SAFE, CLEAN GREEN