

## KENEX EM-110

### Emulsifiable engine cleaner and rubber traces cleaner

#### CHARACTERISTICS

It is an effective degreaser emulsifiable in water, formulated for cleaning of inorganic soil, waste greases, oils, etc. It can also be mixed with diesel or petrol reinforcing its cleaning power.

It's indicated in garages, gas stations, car washes and industry in general, for cleaning of engines, tools, machinery, floors and traces of tire rubber of working machinery in soils industries. It does not attack or dry joints, sleeves, rubber, plastics or other materials.

#### HOW TO USE

It can be used pure, mixed with diesel fuel or oil, either dissolved in water at 15-20 %, depending on the degree of dirt. To get a more viscous emulsion and adherent, first dilute in water at 35-40 %, mix and gradually add the rest of water and shaking.

Apply it by pressure with air pistol, brush or dip, let it act for a long time, then rinse with plenty of water. To clean tar spots on body used pure or diluted in water to 50%.

For cleaning traces of tire rubber apply pure product on traces of rubber, leave a few minutes and rub with a brush or rotary machine. Then wipe the floor manually or with automatic scrubber, but only with water and without using detergent, because the remains of the product initially used will be sufficient to remove rubber residue and dirt from the floor.

#### PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Transparent liquid
Colour	Yellow
Odour	Solvent
pH	Not relevant
Density (20°C)	870 kg/m <sup>3</sup>
Solubility	Soluble in organic solvents and water-emulsifiable.

#### PRESENTATION

10 litres containers

#### PRECAUTIONS

Danger



**Hazard statements:** Aquatic Chronic 3: H411 - Harmful to aquatic life with long lasting effects. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. Eye Dam. 1: H319 - Causes serious eye damage. Flam. Liq. 3: H226 - Flammable liquid and vapour. Skin Irrit. 2: H315 - Causes skin irritation. STOT SE 3: H336 - May cause drowsiness or dizziness. STOT SE 3: H335 May cause respiratory irritation

**Precautionary statements:** P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P280: Wear protective gloves/protective clothing/eye protection/face protection. P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P370+P378: In case of fire: Use ABC powder extinguisher to put it out. P501: Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

**Supplementary information:** EUH066: Repeated exposure may cause skin dryness or cracking. Do not ingest. Keep out of the reach of children. In case of accident, consult to the Medical Service of Toxicological Information Tel. 0034 915620420.

**Substances that contribute to the classification:** Kerosine (petroleum), hydrodesulfurized; Solvent naphtha (petroleum), light arom. < 0.1 % EC 200-753-7; Alcohols, C9-11, branched and linear, ethoxylated; Ethoxylated Undecyl Alcohol.

#### ADDITIONAL INFORMATION

While the above information is correct to our criteria, as the conditions of use of the product are beyond our control, we disclaim any responsibility for incorrect use of the product.