

## KENEX HR-65

### Corrosion inhibitor in water circuits

#### CHARACTERISTICS

KENEX HR-65 is a special formulation to prevent corrosion and scale which are formed in cooling water circuits. It contains inhibitors that protect steel, copper and other nonferrous metals

#### HOW TO USE

Add KENEX HR-65 to the circuit, once is clean, in accordance with the following dosages: Add 60-100 g of product per 1000 liters of recirculating water (45-80 ml per 1000 liters). For a proper performance, the pH of the circuit must be higher than 8 and it is not convenient to have the water hardness at 0 °F.

#### PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid
Colour	Orange
Odour	Odourless
pH (10%)	11
Density (20°C)	1110 kg/m <sup>3</sup>
Solubility	Soluble in water

#### PRESENTATION

20 litres containers

#### PRECAUTIONS

**Supplementary information:** EUH210: Safety data sheet available on request. Do not ingest. Keep out of the reach of children. In case of accident, consult to the Medical Service of Toxicological Information Tel. 0034 915620420.

#### ADDITIONAL INFORMATION

While the above information is correct to our criteria, as the conditions of use of the product are beyond our control, we disclaim any responsibility for incorrect use of the product.