

## KLESING TDV

Green coolant water soluble

### CHARACTERISTICS

Product specially indicated for grinding operations. KLESING TDV allows the lubrication and decreases the risk of breakage of parts, preventing from oxidation of these parts after the mechanization. Thus, it also prevents the wear of the different tools used. It is formulated without organic composts so it prevents from decomposition issues and bad odours.

### HOW TO USE

When KLESING TDV is diluted in any hardness of water, a transparent green solution is obtained. It is used at a dilution of 2-4% in grinding operations and 4-8% in operations of mechanized with tools.

### PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid
Colour	Intense orange
Odour	Odourless
pH (10%)	10
Density (20°C)	1105 kg/m <sup>3</sup>
Solubility	Easily soluble in water

### PRESENTATION

10 litres containers

### PRECAUTIONS

Warning



**Hazard statements:** Acute Tox. 4: H302 - Harmful if swallowed. Eye Irrit. 2: H319 - Causes serious eye irritation.

**Precautionary statements:** P264: Wash thoroughly after use. P280: Wear protective gloves/protective clothing/eye protection/face protection. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P330: Rinse mouth. P337+P313: If eye irritation persists: Get medical advice/attention. P501: Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively. Do not ingest. Keep out of the reach of children. In case of accident, consult to the Medical Service of Toxicological Information Tel. 0034 915 620 420.

**Substances that contribute to the classification:** Sodium nitrite; Diethanolamine.

### ADDITIONAL INFORMATION

While the above information is correct to our criteria, as the conditions of use of the product are beyond our control, we disclaim any responsibility for incorrect use of the product.