

EUROSANEX, S.L.

Pol. Ind. Castilla · Vial 2 - Vial 5

46380 Cheste (Valencia) · Spain

Tel. +34 962 510 407

Fax +34 962 512 521

correo@eurosanex.com

www.eurosanex.com

#### Data sheet

# **NETTION LR-60**

Rubber traces cleaner

## **CHARACTERISTICS**

Effective concentrated cleaner that easily removes traces of tire rubber of working machinery in soils industries.

#### **HOW TO USE**

Apply pure product on traces of rubber, leave a few minutes and rub with a brush or rotary machine. Then wipe the floor manually or with automatic scrubber, but only with water and without using detergent, because the remains of the product initially used will be sufficient to remove rubber residue and dirt from the floor.

# PHYSICAL AND CHEMICAL PROPERTIES

Appearance Transparent liquid

Colour Yellow Odour Solvent Density (20 °C) 790 kg/m³

Solubility Soluble in organic solvents and water-emulsifiable

## PRESENTATION CONATINER

5 litres containers

# **PRECAUTIONS**

Danger



**Hazard statements:** Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. Eye Dam. 1: H318 - Causes serious eye damage. Skin Irrit. 2: H315 - Causes skin irritation. STOT SE 3: H336 - May cause drowsiness or dizziness.



**Precautionary statements:** P280: Wear protective gloves/protective clothing/eye protection/face protection. P301+P310: IF SWALLOWED: Immediately call a POISON CENTER/doctor. P302+P352: IF ON SKIN: Wash with plenty of water. P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P501: Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively. Do not ingest. Keep out of the reach of children. In case of accident, consult to the Medical Service of Toxicological Information Tel. 0034 915620420.



Substances that contribute to the classification: Kerosine (petroleum), hydrodesulfurized (23  $^{\circ}$ C < FP < 60  $^{\circ}$ C); Alcohols, C13-15, branched and linear, ethoxylated; Ethoxylated Undecyl Alcohol.

## ADDITIONAL INFORMATION

While the above information is correct to our criteria, as the conditions of use of the product are beyond our control, we disclaim any responsibility for incorrect use of the product.