

## CHARACTERISTICS

Product specifically formulated as an additive for water in refrigeration systems and /or heating systems in closed circuits in automobiles, boilers, etc., preventing the water from freezing even at temperatures of - 40 ° C. Due to its special formulation prevents limescale and rust in the circuit and therefore prolonging its life.

## HOW TO USE

Drain the cooling circuit completely, filling it afterwards according to the following table, depending on the protection temperature desired.

Temperature (°C)	REFRIGEN (litre)	Water (litre)
- 5	1	4
- 10	1	3
- 15	1	2
- 25	1	1
- 40	1	-----

## PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid
Colour	Green
Odour	Characteristic
pH (10%)	7.7
Density (20°C)	1110 kg/m <sup>3</sup>
Solubility in water	Soluble in water in any proportion

## PRESENTATION CONATINER

10 litres containers

## PRECAUTIONS

Warning



**Hazard indications:** Acute Tox. 4: H302 - Harmful if swallowed. STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral).

**Cautionary advice:** P260: Do not breathe dust/fume/gas/mist/vapours/spray. P270: Do not eat, drink or smoke when using this product. P314: Get medical advice/attention if you feel unwell. P330: Rinse mouth. P501: Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively. Do not ingest. Do not mix with other products. Keep out of the reach of children. In case of accident, consult to the Medical Service of Toxicological Information Tel. 0034 915620420.

**Substances that contribute to the classification:** Ethane-1,2-diol; Sodium nitrite.

## ADDITIONAL INFORMATION

While the above information is correct to our criteria, as the conditions of use of the product are beyond our control, we disclaim any responsibility for incorrect use of the product.