

**TRAVI SL-20****Sealant and anti-graffiti protector****CHARACTERISTICS**

It's formulated for the protection of all type of surfaces (concrete, bricks, marble, granite, etc.), providing excellent waterproof properties, maintaining its effect during long time. It repels water, oil and paintings, protecting the permeability of the substrate, allowing an effective elimination of the graffiti with water (warm up, if possible).

**HOW TO USE**

Clean and let dry the surface. Apply the product with brush, roller or sprayer, depending on the porosity of the surface.

The amount of product to be used will be from 100 to 200 ml per m<sup>2</sup> usually, but it depends on the porosity of the surface:

- Smooth nonporous: 25-50 ml/m<sup>2</sup>
- Smooth porous 100-150 ml/m<sup>2</sup>
- Rough porous 150-200 ml/m<sup>2</sup>.

For porous surfaces, apply two layers, letting dry between both applications. Optimal performance is obtained after 5-7 days. After the elimination of graffiti, treat again the surface with TRAVI SL-20.

**PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	Liquid
Colour	White
Odour	Odourless
pH	7.5
Density (20°C)	1010 kg/m <sup>3</sup> .
Water solubility	Soluble in water

**PRESENTATION**

5 litres container

**PRECAUTION**

**Supplementary information:** EUH210: Safety data sheet available on request. Do not ingest. Keep out of the reach of children. In case of accident, consult to the Medical Service of Toxicological Information Tel. 0034 915620420

**ADDITIONAL INFORMATION**

While the above information is correct to our criteria, as the conditions of use of the product are beyond our control, we disclaim any responsibility for incorrect use of the product.