

CHARACTERISTICS

Professional crystallizer that cleans, covers the pore, waterproofs and polishes calcareous floors: marble, mosaic, polished cement, etc.

Of high performance and fast application, it prepares the floor for further be vitrify with the TRAVI 01 sealant crystalliser providing a better grip, brightness and duration.

Provides a long-lasting and highly resistant hard coating that increases the resistance to the aggressions of the traffic, at the same time that it highlights the color of the floors treated with an intense and long-lasting shine.

HOW TO USE

Shake before use. It is convenient to pre-strip the surface with KENEX DC ALCALINO and with the floor clean and dry deposit small amounts of product on the floor, dealing in areas of about 2 m² with a low speed rotary machine and steel wool disc, making circular passes until the total absorption of the product, repeating if necessary. Performance of 150-200 m²/liter depending on the porosity of the pavement.

It should not be applied in terracotta flooring or wood or use rusty steel wool, because it can cause patches on the pavement.

PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid
Colour	Turquoise
Odour	Odourless
pH	3.2
Density (20°C)	1110 kg/m ³
Water solubility	Soluble in water

PRESENTATION

5 litres container

PRECAUTION

Danger



Hazard statements: Acute Tox. 4: H302 - Harmful if swallowed. Eye Dam. 1: H318 - Causes serious eye damage.

Precautionary statements: P264: Wash thoroughly after use. P280: Wear protective gloves/protective clothing/eye protection/face protection. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310: Immediately call a POISON CENTER or doctor/physician. P330: Rinse mouth. P501: Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively. Do not ingest. Keep out of the reach of children. Restricted to professional users. In case of accident, consult to the Medical Service of Toxicological Information (Spain) tel. 0034 915 620 420.

Substances that contribute to the classification: Magnesium hexafluorosilicate, 6H₂O.

ADDITIONAL INFORMATION

While the above information is correct to our criteria, as the conditions of use of the product are beyond our control, we disclaim any responsibility for incorrect use of the product.