

CHARACTERISTICS

It's formulated specifically as professional crystallizer sealer and polish for floors for calcareous floors: terrazzo, marble, granite, polished concrete, etc.

It covers the surfaces with a crystalline microfilm with long duration and very hard and metallic lustre, obtaining a durable, anti-slip crystallized floor and highly resistant that increases resistance to traffic aggressions, while highlighting the color of floors treated with an intense and lasting shine.

It's waterproof and increases the hardness and strength of the soil, preventing the adherence of dirt on the surface and facilitating the cleaning of floors.

HOW TO USE

Shake before use. It is convenient to pre-strip the surface with KENEX DC ALCALINO and with the floor clean and dry deposit small amounts of product on the floor, dealing in areas of about 2 m² with a low speed rotary machine and steel wool disc, making circular passes until the total absorption of the product, repeating if necessary. Performance of 200-300 m²/liter depending on the porosity of the pavement.

For better and longer lasting shine, apply then the sealant and polishing TRAVI 02.

Do not apply the product with moist soil or debris of acid or alkaline pickling as crystallization may be impossible or yellowing may occur in the final finish.

It should not be applied in terracotta flooring or wood or use rusty steel wool, because it can cause patches on the pavement.

PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Liquid
Colour	Opaque rose
Odour	Odourless
pH (10%)	3
Density (20°C)	1100 kg/m ³
Water solubility	Soluble in water

PRESENTATION

5 litres container

PRECAUTION

Danger



Hazard indications: Acute Tox. 4: H302 - Harmful if swallowed. Eye Dam. 1: H318 - Causes serious eye damage.

Cautionary advice: P264: Wash thoroughly after use. P280: Wear protective gloves/protective clothing/eye protection/face protection. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310: Immediately call a POISON CENTER or doctor/physician. P330: Rinse mouth. P501: Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively. Do not ingest. Keep out of the reach of children. In case of accident, consult to the Medical Service of Toxicological Information Tel. 0034 915620420.

Contains: Magnesium hexafluorosilicate, 6H₂O.

ADDITIONAL INFORMATION

While the above information is correct to our criteria, as the conditions of use of the product are beyond our control, we disclaim any responsibility for incorrect use of the product.